



PROFESSIONAL HEAVY DUTY ANTIFREEZE / COOLANT



PRODUCT GUIDE



ONE FOCUS. HD ENGINE ANTIFREEZE/COOLANT.

HD Expert is focused on formulating heavy duty engine antifreeze/coolants that get the job done – so you can keep doing yours. Our specialized formulas are made for the hardest working heavy duty engines on earth.

ADVANCED COOLANT TECHNOLOGY

HD Expert's team of researchers and technicians have fine-tuned our line-up of HD coolants, each offering the most advanced technology for maximum performance.

CORROSION PREVENTION

A clean engine is a cool engine. Our specialized formulas stop corrosion in its tracks for all cooling-system metals.

THERMAL INTEGRITY

Calibrated to handle the most extreme climate conditions, our formulas enable efficient heat transfer to regulate critical system temperatures.

LONGEVITY

Our coolants combine unique corrosion inhibitors and superior functional additives, providing optimum performance and maximum stability.

CONTAINS:

PRO SHIELD
OAT CORROSION DEFENSE™

HD Expert's proprietary OAT corrosion inhibitor, ProShield™ protects the latest coolant system materials against corrosion and deterioration and provides excellent high temperature aluminum and wet sleeve liner cavitation protection.

- REDUCED NEED FOR COOLANT EXTENDER
- 2-EHA FREE ORGANIC ADDITIVE TECHNOLOGY



	CLASSIC
CORROSION INHIBITOR	CONVENTIONAL
LIQUID COLOR	PURPLE
APPLICATION	Recommended for use where a fully formulated heavy duty diesel coolant is required, including, but not limited to, Caterpillar, Cummins, Detroit Diesel, Ford, Freightliner, GM, International Truck and Engine, Kenworth, Paccar, Peterbilt, Volvo Mack and Western Star.
FORMULATION	LOW SILICATE PHOSPHATE FREE FULLY FORMULATED
SPECIFICATION / PERFORMANCE LEVEL	<p>Meets or exceeds performance requirements:</p> <ul style="list-style-type: none"> • ASTM D3306, D4985, D6210 • AS/NZS 2108.2004 Type A • Caterpillar (other than EC-1) • Cummins 3666132 • DDC 7SE 298, 93K217 • GB 29743-2013 • GM 1825M, 1899M • TMC RP329B <p>Recommended and suitable for use with:</p> <ul style="list-style-type: none"> • Ford ESE-M97B44-A, ESE-M97B44-C • GM Heavy Truck • International Truck and Engine CEMS B-1 • Kenworth RQ26-170-97 • Mack 014GS17004 • New Holland WSN-M97B18-D • PACCAR • Peterbilt 8502.002 • Volvo Heavy Truck • US Fed A-A870-A
RECOMMENDED CHANGE INTERVAL	



PREMIUM	EXTREME	ENDURANCE	EXTRA
HYBRID	PRO SHIELD	PRO SHIELD	PRO SHIELD
RED	RED	GOLD	PALE YELLOW
<p>Older model light and heavy duty diesel applications where an extended service interval is required.</p> <p>Recommended for use in on-road truck, off-road, farm, marine and stationary applications including, but not limited to, Caterpillar, Cummins, Detroit Diesel/MTU, GM Heavy Truck, Freightliner, PACCAR and Volvo Mack.</p>	<p>Heavy duty diesel applications where extended service interval and aluminum compatibility is required. <i>Engineered for new cooling systems.</i></p> <p>Recommended for use in off-road, on-road truck, farm and marine engine applications including, but not limited to, Caterpillar, Cummins, Detroit Diesel/MTU, GM Heavy Truck, Freightliner, PACCAR and Volvo Mack.</p>	<p>Intense heavy duty diesel and natural gas applications where high heat and aluminum protection is required. <i>Engineered for newer cooling systems.</i></p> <p>Recommended for use in all on-road and off-road vehicles including, but not limited to, Caterpillar, Cummins, Detroit Diesel/MTU, GM Heavy Truck, Freightliner, PACCAR/DAF and Volvo Mack.</p>	<p>Full fleet use for ALL VEHICLE TYPES; automotive, light truck & heavy duty, gasoline or diesel including on-road, off road, construction and farm applications or where high heat and aluminum protection is required. <i>Engineered for newer cooling systems.</i></p>
<p>LOW SILICATE PHOSPHATE & AMINE FREE CAT EC-1 COMPATIBLE</p>	<p>NITRITE & MOLYBDATE RICH CAT EC-1 COMPATIBLE • 2-EHA, SILICATE, BORATE, AMINE & PHOSPHATE FREE</p>	<p>SUPERIOR ALUMINUM PROTECTION NO SCA OR EXTENDER NEEDED NITRITE, 2-EHA & SILICATE FREE</p>	<p>COMPATIBLE WITH ALL ENGINE COOLANT TECHNOLOGIES NITRITE, 2-EHA, AMINE & PHOSPHATE FREE</p>
<p>Meets or exceeds performance requirements:</p> <ul style="list-style-type: none"> • ASTM D3306, D4985, D6210, D7583 • AS/NZS 2108.1: 1997 Type A • Cummins 3666132 • DDC 7SE 298, 93K217 • GB 29743-2013 • GM 1825M, 1899M • JIS K2234 • MTU MTL 5048 • TMC RP329B <p>Recommended and suitable for use with:</p> <ul style="list-style-type: none"> • CAT EC-1 • Cummins 14603 • Ford WSS-M97B51-A1 • MAN 324 • MB DBL 7700 • Kenworth RO26-170-97 • Mack 014GS17004 • New Holland WSN-M97B18-D • PACCAR • Peterbilt 8502.002 • Scania 6901 • Volvo Heavy Truck 	<p>Meets or exceeds performance requirements:</p> <ul style="list-style-type: none"> • ASTM D3306, D6210, D7583, D7820 • AS/NZS 2108.2004 Type A • Cummins 3666132 • DDC 7SE 298 • GB 29743-2013 • TMC RP329B, TMC RP338 <p>Recommended and suitable for use with:</p> <ul style="list-style-type: none"> • CAT EC-1 • Cummins 14603 • Freightliner 48-22880 • GM Heavy Truck • International Truck and Engine/Navistar CEMS B-1 • MAN 324 • MB DBL 7700 • MTU MTL 5048 • Kenworth RO26-170-97 • Mack 014GS17009 • PACCAR CS0185 • Peterbilt 8502.002 • Scania TB1451 • Volvo Heavy Truck 	<p>Meets or exceeds performance requirements:</p> <ul style="list-style-type: none"> • ASTM D3306, D6210, D7583, D7820 • AS/NZS 2108.2004 Type A • Cummins 3666132 • DDC 7SE 298, 93K217 • International Truck and Engine / Navistar CEMS B-1 Type III-A • TMC RP329B, TMC RP338 <p>Recommended and suitable for use with:</p> <ul style="list-style-type: none"> • Case New Holland • Cummins 14603 • Freightliner 48-22880 • GM Heavy Truck • JIS K2234 • MAN 324 NF • MB DBL 7700 • MTU MTL 5048 • Kenworth RO26-170-97 • Mack 014GS17004, 014GS17009 • PACCAR CS0185 • DAF MAT 74002 • Peterbilt 8502.002 • Scania TB1451 • Volvo Heavy Truck 	<p>Meets or exceeds performance requirements:</p> <ul style="list-style-type: none"> • ASTM D3306, D4985, D6210, D7583 • AS/NZS 2108.2004 Type A • BRP (Bombardier Recreational Vehicles) • Caterpillar (not EC-1) • Cummins 3666132 • DDC 7SE 298, 93K217 • Kubota • Kobelco • TMC RP329B, TMC RP338 <p>Recommended and suitable for use with:</p> <ul style="list-style-type: none"> • Chrysler MS7170, MS9769 • Cummins 14603 • Ford ESE-M97B44A, WSS-M97B44D, WSS-M97B51-A1 • Freightliner 48-22880 • GM 1825M, 1899M, 6277M, Heavy Truck • JIS K2234 • MAN 324 NF • MB DBL 7700 • MTU MTL 5048 • Kenworth RO26-170-97 • Mack 014GS17004, 014GS17009 • PACCAR CS0185 • DAF MAT 74002 • Peterbilt 8502.002 • Scania TB1451 • Volvo Heavy Truck
<p>UP TO 960,000 KM/600,000 MILES, 12,000 HOURS OR 6 YEARS</p>	<p>UP TO 1,200,000 KM/750,000 MILES, 15,000 HOURS OR 8 YEARS</p>	<p>UP TO 1,600,000 KM/1,000,000 MILES, 20,000 HOURS OR 8 YEARS</p>	<p>AUTOMOTIVE LIGHT DUTY: UP TO 250,000 KM/150,000 MILES OR 5 YEARS HEAVY DUTY DIESEL: UP TO 960,000 KM/600,000 MILES, 12,000 HOURS OR 6 YEARS</p>

CLASSIC

Featuring HD Expert's legacy technology, Classic is a traditional coolant ideally suited for older vehicles.

CLASSIC FORMULATION. EXCELLENT VALUE.

CONVENTIONAL DIESEL

- Low silicate; Phosphate and Amine free
- Aluminum compatible
- CLASSIC Conventional Diesel – recommended for use where a fully formulated heavy duty diesel coolant is required
- DOES NOT require an initial charge of SCA
- For automotive, light duty, heavy duty diesel & natural gas engine applications (on-road truck, off-road, farm equipment)
- Protects heavy duty diesel wet sleeve liners

HD Expert CLASSIC Antifreeze/Coolant is a superior fully formulated traditional engine coolant based on a proprietary formulation of corrosion inhibitors. The low silicate level of this aluminum compatible product allows it to be used in automotive, light duty, heavy duty diesel and natural gas engine applications such as on-road truck, off-road and farm equipment. It is recommended for use where a fully formulated heavy duty diesel coolant is required. This includes, but is not limited to, Caterpillar, Cummins, Detroit Diesel, Ford, Freightliner, GM, International Truck and Engine, Kenworth, Paccar, Peterbilt, Volvo Mack and Western Star.





HEAVY DUTY DIESEL | LIGHT DUTY TRUCK | AUTOMOTIVE

MEETS OR EXCEEDS PERFORMANCE REQUIREMENTS OF:	ASTM D3306, D4985, D6210	AS/NZS 2108.2004 Type A	Caterpillar (other than EC-1)
	Cummins 3666132	DDC 7SE 298, 93K217	GB 29743-2013
	GM 1825M, 1899M	TMC RP329B	
RECOMMENDED AND SUITABLE FOR USE WITH:	Ford ESE-M97B44-A, ESE-M97B44-C	GM Heavy Truck	Kenworth RO26-170-97
		International Truck and Engine CEMS B-1	
	Mack 014GS17004	New Holland WSN-M97B18-D	PACCAR
	Peterbilt 8502.002	Volvo Heavy Truck	US Fed A-A870-A

CANADA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
16-284	Concentrate	3.78 L	4	0-56438-16284-1	400-56438-16284-9
16-474	50-50 premixed	3.78 L	4	0-56438-16474-6	400-56438-16474-4
16-285	Concentrate	9.46 L	2	0-56438-16285-8	500-56438-16285-3
16-475	50-50 premixed	9.46 L	2	0-56438-16475-3	500-56438-16475-8

USA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
86-284	Concentrate	1 gal	4	0-56438-86284-0	400-56438-86284-8
86-474	50-50 pre-diluted	1 gal	4	0-56438-86474-5	400-56438-86474-3

DRUM/TOTE

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
26-289	Concentrate	208 L / 55 gal	NA	0-56438-26289-3	NA
26-479	50-50 premixed	208 L / 55 gal	NA	0-56438-26479-8	NA
26-289-1000	Concentrate	1000 L / 264 gal	NA	0-56438-90787-9	NA
26-479-1000	50-50 premixed	1000 L / 264 gal	NA	0-56438-90788-6	NA

PREMIUM

Hybrid technology offering an extended service life, Premium is designed for both light and heavy duty diesel engines.

YOUR ENGINE DESERVES PREMIUM.

EXTENDED LIFE DIESEL

- Low silicate; Phosphate and Amine free
- CAT EC-1 compatible
- PREMIUM Extended Life Diesel - recommended for use where an extended service interval is required
- DOES NOT require a charge of SCA or coolant extender at initial fill
- Protects all coolant system metals; provides wet sleeve liner cavitation protection
- Up to 960,000 km/600,000 miles, 12,000 hours or 6 years
- For older model light & heavy duty diesel applications (on-road truck, off-road, farm, marine, stationary)

HD Expert PREMIUM Antifreeze/Coolant is a low silicate, nitrite based hybrid technology product that does not require a charge of SCA or coolant extender at initial fill. This product is designed to protect all coolant system metals and provides excellent wet sleeve liner cavitation protection. It is designed for use in older model light and heavy duty diesel applications where an extended service interval is required and is recommended for use in on-road truck, off-road, farm, marine and stationary applications including, but not limited to, Caterpillar, Cummins, Detroit Diesel/MTU, GM Heavy Truck, Freightliner, PACCAR and Volvo Mack.





TRUCK



CONSTRUCTION



AGRICULTURE



MARINE



EQUIPMENT

MEETS OR EXCEEDS PERFORMANCE REQUIREMENTS OF:	ASTM D3306, D4985, D6210, D7583	AS/NZS 2108.1: 1997 Type A	Cummins 3666132
	DDC 7SE 298, 93K217	GB 29743-2013	GM 1825M, 1899M
	JIS K2234	MTU MTL 5048	TMC RP329B
RECOMMENDED AND SUITABLE FOR USE WITH:	CAT EC-1	Cummins 14603	Ford WSS-M97B51-A1
	MAN 324	MB DBL 7700	Kenworth RO26-170-97
	Mack 014GS17004	New Holland WSN-M97B18-D	PACCAR
	Peterbilt 8502.002	Scania 6901	Volvo Heavy Truck

CANADA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
16-734	Concentrate	3.78 L	4	0-56438-16734-1	400-56438-16734-9
16-834	50-50 premixed	3.78 L	4	0-56438-16834-8	400-56438-16834-6
16-835	50-50 premixed	9.46 L	2	0-56438-16835-5	500-56438-16835-0

USA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
86-734	Concentrate	1 gal	4	0-56438-86734-0	400-56438-86734-8
86-834	50-50 pre-diluted	1 gal	4	0-56438-86834-7	400-56438-86834-5

DRUM/TOTE

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
26-739	Concentrate	208 L / 55 gal	NA	0-56438-26739-3	NA
26-839	50-50 premixed	208 L / 55 gal	NA	0-56438-26839-0	NA
26-739-1000	Concentrate	1000 L / 264 gal	NA	0-56438-90789-3	NA
26-839-1000	50-50 premixed	1000 L / 264 gal	NA	0-56438-90790-9	NA

EXTREME

A fortified formula with a long service life, Industry professionals trust Extreme to perform in the harshest off-road environments.

EXTREME NEVER QUILTS.

EXTENDED LIFE DIESEL ENGINEERED FOR NEW COOLING SYSTEMS

- Nitrite & Molybdate rich OAT corrosion inhibitor package
- CAT EC-1 compatible
- 2-EHA, Silicate, Borate, Amine & Phosphate free
- Powered by **ProShield™ OAT Corrosion Defense** – engineered for new cooling systems
- EXTREME Extended Life Diesel – recommended for use in heavy duty diesel applications where extended service interval & aluminum compatibility is required
- Compatible with, but does not necessarily need or require the addition of SCA or Coolant Extenders
- Up to 1,200,000 km/750,000 miles, 15,000 hours or 8 years
- For use in off-road, on-road truck, farm and marine engine applications

HD Expert EXTREME Antifreeze/Coolant is powered by *ProShield™ OAT Corrosion Defense* system, a proprietary organic acid technology (OAT) corrosion inhibitor package with nitrite and molybdate. It is free of amines, borates, phosphates and silicates and DOES NOT contain any 2-EHA. It protects coolant system metals against rust and corrosion and provides excellent aluminum and wet sleeve liner cavitation protection. Designed for use in heavy duty diesel applications where extended service interval and aluminum compatibility is required and recommended for use in off-road, on-road truck, farm and marine engine applications including, but not limited to, Caterpillar, Cummins, Detroit Diesel/MTU, GM Heavy Truck, Freightliner, PACCAR and Volvo Mack.





MINING | CONSTRUCTION | AGRICULTURE | MARINE | TRUCK | EQUIPMENT

MEETS OR EXCEEDS PERFORMANCE REQUIREMENTS OF:	ASTM D3306, D6210, D7583, D7820	AS/NZS 2108.2004 Type A	Cummins 3666132
	DDC 7SE 298	GB 29743-2013	TMC RP329B, TMC RP338
RECOMMENDED AND SUITABLE FOR USE WITH:	CAT EC-1	Cummins 14603	Freightliner 48-22880
	GM Heavy Truck	International Truck and Engine/Navistar CEMS B-1	MAN 324
	MB DBL 7700	MTU MTL 5048	Kenworth RO26-170-97
	Mack 014GS17009	PACCAR CS0185	Peterbilt 8502.002
	Scania TB1451	Volvo Heavy Truck	

CANADA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
16-524	Concentrate	3.78 L	4	0-59934-90593-6	400-59934-90593-4
16-534	50-50 premixed	3.78 L	4	0-59934-90597-4	400-59934-90597-2

USA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
86-524	Concentrate	1 gal	4	0-56438-86524-7	400-56438-86524-5
86-534	50-50 pre-diluted	1 gal	4	0-56438-86534-6	400-56438-86534-4

DRUM/TOTE

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
26-529	Concentrate	208 L / 55 gal	NA	0-59934-90595-0	NA
26-539	50-50 premixed	208 L / 55 gal	NA	0-59934-90599-8	NA
26-529-1000	Concentrate	1000 L / 264 gal	NA	0-59934-90596-7	NA
26-539-1000	50-50 premixed	1000 L / 264 gal	NA	0-59934-90600-1	NA

CONTAINS

PRO SHIELD

OAT CORROSION DEFENSE™

DEFEND



CORROSION
DETERIORATION
RUST

PROTECT



EXTREME TEMPERATURES
ALUMINUM ENGINES
WET SLEEVE LINER CAVITATION

REDUCED NEED FOR COOLANT EXTENDER • 2-EHA FREE ORGANIC ADDITIVE TECHNOLOGY

ENDURANCE

Offering the longest service life possible, Endurance is ideal for on-road, long haul, cross-country usage.

ENDURANCE GOES THE EXTRA MILE.

MAXIMUM SERVICE LIFE DIESEL
ENGINEERED FOR NEWER
COOLING SYSTEMS

- Superior aluminum protection
- No SCA or Extender Needed
- Nitrite, 2-EHA, Silicate Free
- Powered by **ProShield™ OAT Corrosion Defense** – engineered for newer cooling systems
- ENDURANCE Maximum Service Life Diesel – recommended for intense heavy duty diesel & natural gas applications where high heat & aluminum protection is required
- Protects latest coolant system materials against corrosion and deterioration
- Provides excellent CAB flux compatibility and wet sleeve liner cavitation protection
- Up to 1,600,000 km/1,000,000 miles, 20,000 hours or 8 years
- For use in all on-road and off-road vehicles

HD Expert ENDURANCE Antifreeze/Coolant is powered by *ProShield™ OAT Corrosion Defense* system, a proprietary organic acid technology (OAT) corrosion inhibitor package that DOES NOT contain 2-EHA and is nitrite, silicate, borate, amine and phosphate free. Designed for intense heavy duty diesel and natural gas applications where high heat and aluminum protection is required. It protects the latest coolant system materials against corrosion and deterioration and provides excellent CAB flux compatibility and wet sleeve liner cavitation protection. It is recommended for use in all on-road and off-road vehicles including, but not limited to, Caterpillar, Cummins, Detroit Diesel/MTU, GM Heavy Truck, Freightliner, PACCAR/DAF and Volvo Mack.





TRUCK

| AGRICULTURE

| CONSTRUCTION

| MARINE

| MINING

| EQUIPMENT

MEETS OR EXCEEDS PERFORMANCE REQUIREMENTS OF:	ASTM D3306, D6210, D7583, D7820	AS/NZS 2108.2004 Type A	Cummins 3666132
	DDC 7SE 298, 93K217	International Truck and Engine / Navistar CEMS B-1 Type III-A	TMC RP329B, TMC RP338
RECOMMENDED AND SUITABLE FOR USE WITH:	Case New Holland	Cummins 14603	Freightliner 48-22880
	GM Heavy Truck	JIS K2234	MAN 324 NF
	MB DBL 7700	MTU MTL 5048	Kenworth RO26-170-97
	Mack 014GS17004, 014GS17009	PACCAR CS0185	DAF MAT 74002
	Peterbilt 8502.002	Scania TB1451	Volvo Heavy Truck

CANADA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
16-924	Concentrate	3.78 L	4	0-56438-16924-6	400-56438-16924-4
16-914	50-50 premixed	3.78 L	4	0-56438-16914-7	400-56438-16914-5

USA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
86-924	Concentrate	1 gal	4	0-56438-86924-5	400-56438-86924-3
86-914	50-50 pre-diluted	1 gal	4	0-56438-86914-6	400-56438-86914-4

DRUM/TOTE

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
26-929	Concentrate	208 L / 55 gal	NA	0-56438-90791-6	NA
26-919	50-50 premixed	208 L / 55 gal	NA	0-56438-90792-3	NA
26-929-1000	Concentrate	1000 L / 264 gal	NA	0-56438-90793-0	NA
26-919-1000	50-50 premixed	1000 L / 264 gal	NA	0-56438-90794-7	NA

CONTAINS

PRO SHIELD

OAT CORROSION DEFENSE™

DEFEND



CORROSION

DETERIORATION

RUST

PROTECT



EXTREME TEMPERATURES

ALUMINUM ENGINES

WET SLEEVE LINER CAVITATION

REDUCED NEED FOR COOLANT EXTENDER • 2-EHA FREE ORGANIC ADDITIVE TECHNOLOGY

EXTRA

HD Extra is specifically designed for complete mixed fleet use in all makes and models both foreign and domestic, for light duty and heavy duty diesel.


ENGINEERED TO GIVE YOU EXTRA.

MIXED-FLEET GLOBAL EXTENDED LIFE FOR ALL VEHICLES; AUTOMOTIVE, LIGHT TRUCK & HEAVY DUTY DIESEL

- Compatible with all engine coolant technologies
- Nitrite, 2-EHA, Amine & Phosphate Free
- Powered by **ProShield™ OAT Corrosion Defense** - engineered for newer cooling systems
- EXTRA Mixed-Fleet Global Extended Life - recommended for use in all makes and models of passenger vehicles, light duty and heavy duty diesel vehicles (on-road, off road, construction, farm applications)
- Protects against rust and corrosion for all coolant system metals, including aluminum
- Excellent protection against wet sleeve liner cavitation pitting
- Automotive Light Duty: Up to 250,000 km/150,000 miles or 5 years
- Heavy Duty Diesel: Up to 960,000 km/600,000 miles, 12,000 hours or 6 years

HD Expert EXTRA Antifreeze/Coolant is powered by *ProShield™ OAT Corrosion Defense* system, a proprietary organic acid technology (OAT) corrosion inhibitor package that DOES NOT contain 2-EHA and is nitrite, borate, amine and phosphate free. Designed for use in all makes and models of passenger vehicles, light duty and heavy duty diesel vehicles including on-road, off road, construction and farm applications. It provides protection against rust and corrosion for all coolant system metals, including aluminum, excellent protection against wet sleeve liner cavitation pitting and is compatible with all aluminum radiators found in today's engine cooling systems.





HEAVY DUTY DIESEL | LIGHT DUTY TRUCK | AGRICULTURE | AUTOMOTIVE | EQUIPMENT

MEETS OR EXCEEDS PERFORMANCE REQUIREMENTS OF:	ASTM D3306, D4985, D6210, D7583	AS/NZS 2108.2004 Type A	BRP (Bombardier Recreational Vehicles)
	Caterpillar (not EC-1)	Cummins 3666132	DDC 7SE 298, 93K217
	Kubota	Kobelco	TMC RP329B, TMC RP338
RECOMMENDED AND SUITABLE FOR USE WITH:	Chrysler MS7170, MS9769	Cummins 14603	Ford ESE-M97B44A, WSS-M97B44D, WSS-M97B51-A1
	Freightliner 48-22880	GM 1825M, 1899M, 6277M, Heavy Truck	JIS K2234
	MAN 324 NF	MB DBL 7700	MTU MTL 5048
	Kenworth RO26-170-97	Mack 014GS17004, 014GS17009	PACCAR CS0185
	DAF MAT 74002	Peterbilt 8502.002	Scania TB1451
	Volvo Heavy Truck		

CANADA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
16-314	Concentrate	3.78 L	4	0-56438-16314-5	400-56438-16314-3
16-324	50-50 premixed	3.78 L	4	0-56438-16324-4	400-56438-16324-2
16-325	50-50 premixed	9.46 L	2	0-56438-16325-1	500-56438-16325-6

USA

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
86-324	50-50 pre-diluted	1 gal	4	0-56438-86324-3	400-56438-86324-1

DRUM/TOTE

ITEM NO.	FORMULATION	CONTAINER SIZE	CASE PACK	UPC	SCC
26-319	Concentrate	208 L / 55 gal	NA	0-56438-90795-4	NA
26-329	50-50 premixed	208 L / 55 gal	NA	0-56438-90796-1	NA
26-319-1000	Concentrate	1000 L / 264 gal	NA	0-56438-90797-8	NA
26-329-1000	50-50 premixed	1000 L / 264 gal	NA	0-56438-90798-5	NA

CONTAINS **PRO SHIELD**
OAT CORROSION DEFENSE™

DEFEND

	CORROSION
	DETERIORATION
	RUST

PROTECT

	EXTREME TEMPERATURES
	ALUMINUM ENGINES
	WET SLEEVE LINER CAVITATION

REDUCED NEED FOR COOLANT EXTENDER • 2-EHA FREE ORGANIC ADDITIVE TECHNOLOGY

THE HD ENGINE COOLANT EXPERTS.

From start-to-finish HD Expert's team of specialists are focused on one thing - making the best HD engine coolants for all heavy duty engines. From our proprietary formulations and custom blending to high-volume packaging and delivery, our global facilities produce the highest quality HD coolants 24/7. Large-scale capacity, advanced coolant technology and dedicated HD experts who have your back make HD Expert the ultimate source for professional heavy duty coolant.

FACTS AT A GLANCE:

Proprietary formulas developed by expert engineers

Batch-tested to ensure consistent performance

Meets or exceeds OE coolant specifications

In-house produced, never sourced



WARRANTY PROGRAM

Visit HDExpert.com to order your test kit.

As the HD Experts, we stand behind and **support our products by offering a Limited Warranty**, providing you peace of mind in the use of our antifreeze/ coolant. This warranty is supported by HD Expert's advanced testing laboratory that can analyze the condition of your engine's coolant across a multitude of checkpoints in support of our program. A complimentary detailed analysis report guarantees you have the best HD coolant for your engine throughout the lifetime of product use. Visit our website for further warranty program details including terms and conditions that apply.





Recochem Inc.
Your Partner in Formulating Solutions
www.recochem.com

GET MORE
HDExpert.com